



TUNNEL PASTEURIZER & CAN WARMER

Standard Features

- Dynamic Active Control System
- Chemical Dosing System
- Infeed and Outfeed Conveyors

System Capabilities

- Products: Beer, Cider, CSD, Energy, Coffee, Cannabis
- Can Type: Aluminum Beverage Cans - Standard - Sleek - Slim
- Capacity: 50-400 CPM
- Construction: 304 Stainless Steel
- Filling Temp: <4°C
- PLC/HMI: Siemens
- Electrical: 380/480 Volts 60/50HZ 3 Phase
- Pasteurization Cycle: Up to 100 PU
- Compressed Air: Free of oil and water, Pressure 6-8 Bar, 400-600 l/h
- Filtered Water: 2-3 bar, 300 l/h PH<7

Component Features

- Level Sensors: Endress & Hauser
- Conveyor: Rexnord & System Plast
- Pumps: Grundfos Stainless Steel
- Electro Components: Schneider Electric
- Heat Exchangers: Soundex
- Pneumatics: SMC
- Steam Regulating Valves: Samson
- Manholes: Zorzini
- Shaft Bearing: FAG
- Motor driving Gear: SEW

CORPORATE

3759 N. Ravenswood Ave.
Suite 223
Chicago, IL 60613

CONTACT

www.palmercanning.com
+1 (773) 394-4913
info@palmercanning.com

MANUFACTURING

3204 Olympia Drive
Suite A & B
Lafayette, IN 47909

